



## RLC- BF 2040

- Excellent picture quality in Approx. 2 Megapixel,
- 2 Megapixel (1920 x 1080) maximum resolution,
- Three codecs (H.264, MPEG-4, MJPEG) with dual streaming Capability,
- ICR Day/Night function,
- Maple Series.

FULL HD  
1080

ONVIF



#### ■ CMOS Sensor

CMOS sensors give highest picture quality as well as the best sensitivity at both bright and dark locations. They perform on-chip analog to digital signal conversion and two-step noise reduction in parallel on each column of the sensor. This can help to reduce the amount of "seen" pixels when you zoom in on a photo.

#### ■ ONVIF

The Open Network Video Interface Forum (ONVIF) is a global and open industry forum which its goal is to facilitate the development and use of a global open standard for the interface of physical IP-based security products. RedLeaf is a member of ONVIF.

#### ■ Power over Ethernet (PoE)

With PoE a single cable to provide both data connection and electrical power to electronic devices.

PoE allows for great reductions in installation costs as there is no need to install separate power cables for the camera.

#### ■ The Best Possible Image

It is always important to produce the best possible image considering the environmental conditions.

Our expertise is to process the input light by means of a high quality lens, a sensitive image sensor and a powerful DSP processor to produce a crystal clear output image which is superior to any other solution currently available in the market.

#### ■ Vivid Pictures in Darkness

A high percentage of unwanted events happen at night or in low-light conditions. This puts the priority of having a high performance security solution in low light conditions to a very high level. RedLeaf cameras have an unprecedented image quality independent of the lighting conditions, and provide a lucid image at very low lux levels.

## Technical Specifications

### RLC-BF 2040

Camera	
Image device	1/3- type CMOS
Number of effective pixels	2 Megapixel
Minimum illumination	Color: 0.1 lx, BW : 0.005 lx, 0lx IR ON
Electronic shutter speed	1/1 to 1/10,000 s
Gain control	Auto/Manual
Focal length	3 ~ 9 mm
Powered zoom	Yes (easy zoom)
Powered focus	Yes (easy focus)
Exposure control	Full auto, Shutter priority, Iris priority, Manual
White balance mode	Auto, ATW, Indoor, Outdoor, One-push, manual, Sodium vapour lamp
F-number	F1.6 to F3.5
Camera features	
Day/Night	Yes (IR-cut Filter)
WDR+	Yes (90dB)
Noise reduction	Yes (SDNR)
Image	
Codec image size(HxV)	Full HD(1920x1080) /1.3M (1280x1024) / 1.2M (1280x960) HD (1280x720) / D1 (704x576) / CIF (352x288)
Video compression format	H.264, MPEG-4,MJPEG
Codec streaming capability	Dual streaming
Maximum frame rate	30 fps (H.264) / 30 fps(MPEG-4) / 30 fps (MJPEG)
Audio	
Audio compression	G.711 / G.726
Network	
Protocols	IPv4,IPv6,TGP,UDP,ARP,ICMP,IGMP,HTTP,HTTPS,FTP (client/server), SMTP, DHCP, DNS,NTP, RTP/RTCP,RTSP,SNMP (MIB-2)
ONVIF software	Yes (Ver. 2.0)
Number of clinets	20
Authentication	IEEE802.1x
Interface	
Local recording	SD memory card x1(compatible with the SD/SDHC standards, max 32GB)
Ethernet	10BASE - T/ 100BASE-TX (RJ-45)
Sensor input	2
Alarm output	1
External microphone input	mini-jack (mono)
Audio line output	mini-jack (mono), max output level:1Vrms
Analog video output	Yes 1*BNC (75Ω)
General	
Weight	0.7 KG
Dimension(WxDxHmm)	75 x 150 x 65 mm
Power requirements	PoE, DC12V, AC24V
Outdoor	No
Operating temperature	-5°C~50°C
Safety regulation	UI2044, FCC 158 Class A, IC Class A,IEC60950-1, EN55022(A)+EN55024+EN50130-4, VCCI Class A, C-Tick class A
System Requirements	
Operating system	Windows XP™ - Professional Edition Windows Vista™ (32/64bit) - Ultimate, Business Edition Windows 7 (32/64bit) - Ultimate, Professional Edition
Processor	Windows 8 (32/64bit) – Pro Edition
Memory	Intel Core2 Duo 2.33 GHz Or higher
Web browser	2GB or more Microsoft Internet Explorer® Ver. 6.0 and higher Google Chrome® Ver.4.0 and higher (Plug-in free viewer only) Firefox® Ver.3.5 and higher (Plug-in free viewer only) Safari® Ver.4.0 and higher (Plug-in free viewer only)

## Dimensions

