



RLC- RF 3015

- High-quality 1080p Full HD picture quality at 30fps
- Powerful 30x optical Zoom and 16x digital Zoom
- Three codecs (H.264,MPEG-4, MJPEG) with dual streaming Capability
- True day/ night function and IP 67 all environment protection
- High Speed 360 degrees endless rotation with 400 degree/ Second pan Speed
- Maple Series.

FULL HD
1080

360°
Rotation

ONVIF



■ “Exmor” CMOS Sensor

Exmor sensors give highest picture quality as well as the best sensitivity at both bright and dark locations.

They perform on-chip analog to digital signal conversion and two-step noise reduction in parallel on each column of the CMOS sensor. This can help to reduce the amount of "seen" pixels when you zoom in on a photo.

■ ONVIF

The Open Network Video Interface Forum (ONVIF) is a global and open industry forum which its goal is to facilitate the development and use of a global open standard for the interface of physical IP-based security products. RedLeaf is a member of ONVIF.

■ Analog Video Output

This old-fashioned analog video output helps the installer to quickly and easily apply the required first-run settings to the camera.

■ The Best Possible Image

It is always important to produce the best possible image considering the environmental conditions.

Our expertise is to process the input light by means of a high-quality lens, a sensitive image sensor and a powerful DSP processor to produce a crystal clear output image which is superior to any other solution currently available in the market.

■ Vivid Pictures in Darkness

A high percentage of unwanted events happen at night or in low-light conditions. This puts the priority of having a high performance security solution in low light conditions to a very high level. RedLeaf cameras have an unprecedented image quality independent of the lighting conditions, and provide a lucid image at very low lux levels.

FULL HD
1080

360°
Rotation

ONVIF

Technical Specifications

RLC-RF 3015

Camera	
Image device	1/3 Exmor CMOS
Number of effective pixels	Approx. 3.2 Megapixel
Minimum illumination	Color: 0.045 Lux, BW: 0.005 Lux
Electronic shutter speed	1/1 to 1/30,000 s
Gain control	Auto/Manual
Exposure control	Full auto, Shutter priority, Iris priority, Manual
White balance mode	Auto, ATW, Indoor, Outdoor, Manual,
Zoom ratio	Optical zoom 30 x, Digital zoom 16 x, Total zoom 480 x
Horizontal viewing angle	58.9 to 2.1 degrees
Focal length	f=4.3 to 129 mm
f-number	F1.6 to F5
Minimum object distance	10mm (wide) to 1200mm (tele)
Pan angle	360 degrees endless rotation
Pan Speed	400 degrees/s (max)
Tilt angle	180 degrees(with e-flip)
Tilt speed	300 degrees/s (max)
Preset position	256 positions
Tour	5
Camera Features	
Day / Night	Yes (IR-cut Filter)
WDR+	Yes (90dB)
Noise reduction	Yes (SDNR)
PTZ	
Codec image size(HxV)	Full HD(1920x1080) /1.3M (1280x1024) / 1.2M (1280x960), HD (1280x720) / D1 (704x576) / CIF (352x288)
Video compression format	H.264, MPEG-4, MJPEG
Codec streaming capability	Dual streaming
Maximum frame rate	30 fps (H.264) / 30 fps (MPEG-4) / 30 fps (MJPEG)
Audio	
Audio compression	G.711/G.726
Network	
Protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, FTP (client/server), SMTP, DHCP,DNS, NTP, RTP/RTCP, RTSP, SNMP(MIB-2)
ONVIF software	Yes (Ver. 2.0)
Number of clients	20
Authentication	IEEE802.1X
Interface	
Local recording	SD memory card x 1 (Compatible with the SD/SDHC standards) max 32GB
Analog video output	Yes 1*BNC (75 Ω)
Sensor input	2
Alarm out put	1
External microphone input	Mini-jack (monaural)
Audio line output	Mini-jack (monaural), Max ouput level: 1 Vrms
Ethernet	10BASE-T / 100BASE-TX (RJ-45)
General	
Weight	5.3 KG
Dimensions (øx H mm)	235 x 320 mm
Power requirements	AC 24V/3A(±10%)
Outdoor	Yes
Power consumption	15W(Indoor), 40W(Outdoor, heater on)
Operating temperature	-40°C ~ 60°C
Safety regulation	UL2044, FCC 15B Class A, IC Class A, IEC60950-1, EN55022(A)+EN55024+EN50130-4, VCCI Class A, C-Tick Class A
Working humidity	<90%
Protection level	IP 67
System Requirements	
Operating system	Windows XP™ - Professional Edition Windows Vista™ (32/64bit) - Ultimate, Business Edition Windows 7 (32/64bit) - Ultimate, Professional Edition Windows 8 (32/64bit) – Pro Edition
Processor	Intel Core2 Duo 2.33 GHz or higher
Memory	2 GB or moreMicrosoft Internet Explorer® Ver. 6.0 and higher
Web browser	Microsoft Internet Explorer® Ver. 6.0 and higher Google Chrome® Ver.4.0 and higher (Plug-in free viewer only) Firefox® Ver.3.5 and higher (Plug-in free viewer only) Safari® Ver.4.0 and higher (Plug-in free viewer only)

Dimensions

