

NVR 4009U-MF

9 Channel Network Video Recorder



FEATURES:

RLN-4009U-MF standalone rack-mount network video recorder (NVR) supports 9-channel network cameras with MJPEG, MPEG4 and H.264 recording with 4 high-speed 3.5-inch SATA II hard disks for flexible long-term recording. The hard disks are hot swappable so you don't need to turn off the system to add or replace the hard disks. The maximum allowed capacity of each hard disk is 4 TB.

This NVR includes several management options with enterprise-class video viewing and automated monitoring software. The multi-server monitoring feature of this NVR allows you to simultaneously monitor up to 9 IP cameras from multiple NVR servers.

RedLeaf's NVRs can record video from IP cameras located in local or remote sites into a dedicated HDD storage without turning on a computer. The NVRs support real-time monitoring and playback anytime, anywhere, via a web browser. High-resolution local display can be achieved by using the HDMI port to connect the NVR to an HDMI monitor or TV for monitoring content in Full HD (1920 x 1080) resolution.

Another feature is the intelligent video analytics feature, which provides you with security features such as motion detection, foreign object, missing object, out of focus, and camera occlusion. Additionally, it also offers schedule recording, alarm recording, alarm recording schedule, motion detection recording, and pre/post-alarm recording. Moreover, this NVR ensures data security with RAID (RAID 0, 1, 5) for maximum data reliability in case that any type of hard disk failure occurs.

RLN-4009U-MF

System		Network	
CPU	Intel® Core™ i3	Protocol	TCP/IP, UDP, RTP/RTCP/RTSP, FTP, Telnet, SNMP, HTTP, DHCP, DDNS
Operating System	Embedded Windows 7	Number of Clients	4 Users
Motherboard	Embedded Board	Motion Detection & Alarm	
Memory	4GB DDR3 (up to 8GB expansion option)	Motion Detection	Yes
Case	Hot-dipped galvanized sheet, Stainless steel, High-precise aluminum	Interface	
Fan	Dual ball screw bearing fan, MTBF>100,000h	Front Cover	Hot swap support
Interface	Local GUI	Ethernet Port	2* RJ-45 ports (10/100/1000M)
Video & Audio		USB	4 USB2.0, 2 USB3.0 ports
Number of Input Channels	9 Ch.	General	
Playback	Full-HD / HD / D1	Power Requirements	100V-240Vac
Audio	Mic in, Audio out	Power Consumption	< 70W (HDD Included)
Recording		Operating Temperature	-10°C~55°C
Recording Mode	Manual, Schedule(Continuous, Video detection (Motion detection, Camera blank), Alarm)	Working Humidity	10%~80% (non-condensation)
Recording Resolution	8M, 5M, 3M, 1080P, 720P, 960H, D1, CIF, QCIF, VGA	Dimensions (W×D×H)	650x430x44 mm
Alarm Recording	Video loss, Camera blank, Motion detection, External alarm	Weight	7.5 Kg
Backup Mode	Network download / USB HDD / USB CD&DVD-RW(Optional)	Installation	Rack mount (1 Unit)
Video Bit Rate	64Kbps~8Mbps		
Audio Bit Rate	32Kbps~64Kbps		
Display			
Video Output	1X HDMI / 1 VGA		
Multi-Screen Display	1st screen: 1/4/6		
Privacy masking	4 customized zones with privacy masking for each area		
Hard Disk			
Hard Disk	2X SATAIII, 2X SATAII		
HDD Mode	Single, RAID 0, RAID 1, RAID 5		
HDD Installation	Independent HDD rack, Hot swap support		

RLN-4009U-MF 9 Channel Network Video Recorder

