

# NVR 5024-AF

## 24 Channel Network Video Recorder



### FEATURES:

RLN-5024-MF Vertical Desktop network video recorder (NVR) supports 24-channel network cameras with MPEG4 and H.264 recording with 5 high-speed 3.5-inch SATA II hard disks for flexible long-term recording. The hard disks are hot swappable so you don't need to turn off the system to add or replace the hard disks. The maximum allowed capacity of each hard disk is 3 TB.

This NVR includes several management options with enterprise-class video viewing and automated monitoring software. The multi-server monitoring feature of this NVR allows you to simultaneously monitor up to 24 IP cameras from multiple NVR servers.

RedLeaf's NVRs can record video from IP cameras located in local or remote sites into a dedicated HDD storage without turning on a computer. The NVRs support real-time monitoring and playback anytime, anywhere, via a web browser. High-resolution local display can be achieved by using the HDMI port to connect the NVR to an HDMI monitor or TV for monitoring content in Full HD (1920 x 1080) resolution.

The Central Processing Unit (CPU) of this NVR is an Intel Dual Core for high performance video processing and multitasking. This NVR delivers a throughput of 96 Mb/s, allowing for seamless multi-user and multichannel video playback

# RLN-5024-AF

System		Network	
CPU	Intel® Dual Core™	Protocol	TCP/IP, UDP, RTP/RTCP/RTSP, FTP, Telnet, SNTP, HTTP, DHCP, DDNS
Operating System	Embedded LINUX	Ethernet Port	1* RJ-45 port (10/100/1000M)
Motherboard	Embedded Board	Number of Clients	20 Users
Memory	2GB DDR3	<b>Motion Detection &amp; Alarm</b>	
Case	Hot-dipped galvanized sheet, Stainless steel, High-precise aluminum	Motion Detection	Zones: 396 (22×18), Sensitivity: 1~6 (level 6 is highest)
Fan	Dual ball screw bearing fan, MTBF>100,000h	Alarm Input	From 16ch, Green terminal interface
Interface	Local GUI / Web GUI	Relay Output	To 4ch, Relay contact, NO/NC programmable, green terminal
<b>Video &amp; Audio</b>		<b>Interface</b>	
Number of Input Channels	24 Ch.	Front Cover	Hot swap support
Playback	Full-HD / HD	USB	3 USB2.0 ports (1 on the front-panel, 2 on the rear panel)
Audio	Mic in, Audio out	eSATA	1 eSATA (for Video Backup)
<b>Recording</b>		<b>General</b>	
Recording Mode	Manual, Schedule(Continuous, Video detection (Motion detection, Camera blank), Alarm)	Power Requirements	100V-240VAC
Recording Resolution	3M, 1080P, 720P, 960H	Power Consumption	< 100W (HDD Included)
Alarm Recording	Video loss, Camera blank, Motion detection, External alarm	Operating Temperature	-10°C~55°C
Backup Mode	Network download / USB HDD / USB CD&DVD-RW / eSATA Device	Working Humidity	10%~90% (non-condensation)
Video Bit Rate	64Kbps~8Mbps	Dimensions (W×D×H)	200x380x300 mm
Audio Bit Rate	32Kbps~64Kbps	Weight	6 Kg
<b>Display</b>		Installation	Vertical Desktop
Video Output	1X HDMI / 1 VGA		
Multi-Screen Display	1st screen: 1/4/6/8/9/16/24		
Privacy masking	4 customized zones with privacy masking for each area		
<b>Hard Disk</b>			
Hard Disk	5X SATAII		
HDD Installation	Hot swap support (Each Port Max 3TB)		

## RLN-5024-AF 24 Channel Network Video Recorder

